

Pneumatic Torque Wrenches

Series:	ITN
Type:	Pneumatic



1 New advanced motor enables faster operation at a lower noise

2 Ergonomic pistol grip reduces operator strain; thus resulting in increased productivity

✓ Customised ITN pneumatic torque wrenches can be made against order

✓ All ITN pneumatic torque wrenches come with a Reaction Arm

! The maximum operating pressure of all the Pneumatic Torque Wrenches is 6.2 bar / 90 psi

Also available in sets for ordering convenience

(ITN Wrench + Digital FRL + Couplers + Hose)



Aa Model	Torque Range	Square Drive	Non-Load Speed	Accuracy	Repeatability	Length	Height	Weight
ITN5	100 Nm - 500 Nm	3/4"	50 RPM	+/- 4%	+/- 2%	170 mm	185 mm	4 kg
ITN10	150 Nm - 1,000 Nm	3/4"	28 RPM	+/- 4%	+/- 2%	250 mm	185 mm	4.8 kg
ITN15	200 Nm - 1,500 Nm	1"	21 RPM	+/- 4%	+/- 2%	260 mm	185 mm	5.2 kg
ITN20	300 Nm - 2,000 Nm	1"	15 RPM	+/- 4%	+/- 2%	260 mm	185 mm	5.5 kg
ITN30	500 Nm - 3,000 Nm	1"	10 RPM	+/- 4%	+/- 2%	340 mm	185 mm	7.5 kg
ITN40	700 Nm - 4,000 Nm	1 1/2"	7 RPM	+/- 4%	+/- 2%	340 mm	185 mm	9.5 kg
ITN60	1,000 Nm - 6,000 Nm	1 1/2"	5 RPM	+/- 4%	+/- 2%	380 mm	185 mm	14 kg
ITN80	2,000 Nm - 8,000 Nm	1 1/2"	4 RPM	+/- 4%	+/- 2%	380 mm	185 mm	18 kg
ITN100	2,000 Nm - 10,000 Nm	1 1/2"	3 RPM	+/- 4%	+/- 2%	390 mm	185 mm	20 kg
ITN120	3,500 Nm - 12,000 Nm	1 1/2"	2 RPM	+/- 4%	+/- 2%	395 mm	185 mm	21 kg

+ Frequent Add-On

(Socket)



+ Frequent Add-On

(Square Drive Adaptor)

