

Electric Torque Wrenches

Series:	ITD
Type:	Electric



1

New advanced motor enables faster operation at a lower noise

2

Large LCD which displays torque and other critical information

3

Accurate torque setting every 10 Nm with in-built controls under the LCD display

3

Ability to display torque on the display in Nm & Ft Lbs

4

ITD-A models offer greater flexibility in areas with space restrictions



Customised ITD electric torque wrenches can be made against order



The rated voltage of the Electric Torque Wrenches is 220V, 50/60 Hz



Available in carrying case for convenience



Has a Built-in LCD display facing the operator which displays torque and other critical information



Aa Model	≡ Min. Torque	≡ Max. Torque	≡ Square Drive	≡ Non-Load Speed	≡ Accuracy +/-	≡ Repeatability +/-	≡ Length	≡ Width	≡ Weight
<u>ITD8S</u>	150 Nm	800 Nm	3/4"	40 RPM	2%	1%	385 mm	240 mm	5.5 kg
<u>ITD20S</u>	350 Nm	2,000 Nm	3/4"	14 RPM	2%	1%	400 mm	240 mm	6 kg
<u>ITD30S</u>	600 Nm	3,000 Nm	1"	6.5 RPM	2%	1%	430 mm	240 mm	9.8 kg
<u>ITD40S</u>	800 Nm	4,000 Nm	1"	5.5 RPM	2%	1%	430 mm	240 mm	10 kg
<u>ITD60S</u>	900 Nm	6,000 Nm	1 1/2"	4 RPM	2%	1%	480 mm	240 mm	13.3 kg
<u>ITD80S</u>	1,500 Nm	8,000 Nm	1 1/2"	3 RPM	2%	1%	500 mm	240 mm	16 kg
<u>ITD100S</u>	2,000 Nm	10,000 Nm	1 1/2"	2.5 RPM	2%	1%	510 mm	240 mm	18 kg
<u>ITD150S</u>	2,500 Nm	15,000 Nm	1 1/2"	1.5 RPM	2%	1%	530 mm	240 mm	22 kg

Aa Model	≡ Min. Torque	≡ Max. Torque	≡ Square Drive	≡ Non-Load Speed	≡ Accuracy +/-	≡ Repeatability +/-	≡ Length	≡ Width	≡ Weight
<u>ITD8A</u>	150 Nm	800 Nm	3/4"	40 RPM	2%	1%	410 mm	240 mm	6.5 kg
<u>ITD20A</u>	350 Nm	2,000 Nm	3/4"	14 RPM	2%	1%	425 mm	240 mm	7 kg
<u>ITD30A</u>	600 Nm	3,000 Nm	1"	8.5 RPM	2%	1%	455 mm	240 mm	10.8 kg
<u>ITD40A</u>	800 Nm	4,000 Nm	1 1/2"	5.5 RPM	2%	1%	455 mm	240 mm	11 kg
<u>ITD60A</u>	900 Nm	6,000 Nm	1 1/2"	4 RPM	2%	1%	505 mm	240 mm	14.3 kg
<u>ITD80A</u>	1,500 Nm	8,000 Nm	1 1/2"	3 RPM	2%	1%	525 mm	240 mm	17 kg
<u>ITD100A</u>	2,000 Nm	10,000 Nm	1 1/2"	2.5 RPM	2%	1%	535 mm	240 mm	19 kg
<u>ITD150A</u>	2,500 Nm	15,000 Nm	1 1/2"	1.5 RPM	2%	1%	555 mm	240 mm	23 kg

+ Frequent Add-On

(Socket)



+ Frequent Add-On

(Square Drive Adaptor)

