

Schedule 40 PVC Socket Ball Valve

Socket Connection. EPDM Seal and O-ring. Tee Handle.

Testing Pressure 225 psi at 73F, Working Pressure 150 psi at 73F. Rated Temperature Range at 40F to 125F Continuous up to 140F.

**Standards
Placeholder**



Size	Item	Inner Case	Master Case	MC Weight
1/2"	400-005S	25	100	18.00
3/4"	400-007S	25	100	29.00
1"	400-010S	25	100	49.00
1 1/4"	400-012S	25	100	67.00
1 1/2"	400-015S	25	50	46.00
2"	400-020S	12	24	33.84
2 1/2"	400-025S	6	18	51.48
3"	400-030S	2	2	6.66
4"	400-040S	1	1	9.46
6"	400-060S	1	1	25.00

Schedule 40 PVC Threaded Ball Valve

Threaded Connection. EPDM Seal and O-ring. Tee Handle.

Testing Pressure 225 psi at 73F, Working Pressure 150 psi at 73F. Rated Temperature Range at 40F to 125F Continuous up to 140F.

**Standards
Placeholder**



Size	Item	Inner Case	Master Case	MC Weight
1/2"	401-005T	25	100	18.00
3/4"	401-007T	25	100	29.00
1"	401-010T	25	100	49.00
1 1/4"	401-012T	25	100	67.00
1 1/2"	401-015T	25	50	46.00
2"	401-020T	12	24	33.84
2 1/2"	401-025T	6	18	51.48
3"	401-030T	2	2	6.66
4"	401-040T	1	1	9.46

2" inch PVC Wafer Style Butterfly Valve

EPDM Liner, PVC Disc, Lever Handle.

Max pressure 150 psi, Temp range 40F to 140F.

**Standards
Placeholder**



Size	Item	Inner Case	Master Case	MC Weight
2"	405-020	1	10	37.50
2 1/2"	405-025	1	10	40.00
3"	405-030	1	8	28.00
4"	405-040	1	5	29.00
5"	405-050	1	3	27.00
6"	405-060	1	2	22.00
8"	405-080	1	1	19.00
10"	405-100	1	1	52.00